

# 03-SENSE-00 Edge Sensor

# Description

Delta Controls' award-winning 03® Sense standalone multisensor uses industry-leading sensor fusion technology to deliver the most accurate view of an interior space available on the market.

Integrating temperature, humidity, motion, sound, light, and occupant sensing in a single device, the 03 uses machine learning to provide fast, accurate feedback on the monitored space.

The O3 is easy to install and can be configured out of the box with just a smartphone.





#### **Application**

With support for BACnet, MQTT, and BLE protocols, the 03 Sense is an open platform IoT device that can integrate with almost any system.

#### **Features**

- Composite temperature, humidity, PIR motion, sound, light, and occupant sensors combined in a single device
- User feedback via speaker and fullcolor LED ring with customizable audio tones and colors
- Dual Ethernet connection for daisychaining in large spaces; provides pass-through communication even during power outages
- ► Configuration via mobile app
- ► BLE API for developing custom apps

#### Specifications

#### **Temperature Sensors**

Composite temperature value  $\pm 0.5$ °C ( $\pm 1.0$ °F) typical with calibration

Digital temperature sensor  $\pm 0.5$ °C ( $\pm 1.0$ °F)

Infrared temperature sensor ±1.0°C (±1.8°F) typical

#### **Humidity Sensor**

Accuracy ±3% for 20% to 80% RH @ 15°C to 30°C (59°F to 86°F)

#### Motion Sensor

Passive infrared (PIR) motion sensor

## Motion sensing range:

9.1 m (30 ft) diameter @ 4.6 m (15 ft) mounting height

5.5 m (18 ft) diameter @ 2.4 m (8 ft) mounting height

#### **Light Sensor**

 $\pm$ (6+5% reading) lx

# Occupant Sensor

PIROE (passive infrared occupancy estimation) motion sensor

# **Audio Input**

2 microphones for acoustic occupancy detection

#### **LED Ring**

Full color ring with 12 RGB LEDs

#### **Audio Output**

1.0 W mono speaker for tones and audio output

## Connectors


Removable screw-type terminal connectors



# 03 Sense


# 03-SENSE-00 Edge Sensor


#### **Dimensions**



# Passive Infrared Motion Coverage

Mounting Height	PIR Sensing Range
4.6 m (15 ft)	9.1 m (30 ft)
2.4 m (8 ft)	5.5 m (18 ft)





# Ordering

Order the O3 Sense using the following product number:

331738	03-SENSE-00	Multisensor (temperature, humidity, light, motion, occupancy), Bluetooth, LED ring, microphone and speaker, with mounting plate
331758	03-SENSE-00-B	Multisensor (temperature, humidity, light, motion, occupancy), black plastic, Bluetooth, LED ring, microphone and speaker, with mounting plate

# Specifications (Continued)

# Wiring Class

Class 2 / SELV

#### Powe

24 VDC (20–28 VDC), 2 W typical, 9 W max, Class 2

## Technology

Arm® Cortex®-A7 MPU + Cortex-M4 MCU 256 DDR3L RAM 4 GB eMMC flash memory Real-time clock (RTC) Supercapacitor power backup for RTC

#### **Communication Ports**

Dual Ethernet (10/100Base-T)

#### **Interfaces and Protocols**

BACnet (BACnet/IP, BACnet/Ethernet)
MQTT

BLE 5.0

#### **Ambient Rating**

0°C to 45°C (32°F to 113°F) 10% to 95% RH (non-condensing)

# Dimensions

180 × 41.2 mm (7.1 × 1.6 in.)

#### Weight

350 g (0.77 lb)

#### Compliance

CE FCC/IC

NCC (in progress)

# Listings

cULus 916 Listed

Updated January 2025

Subject to change without notice.



